

## Product Description

CHARING<sup>®</sup> HP D200MPS-B is high viscosity construction grade hydroxypropyl methyl cellulose widely used in construction paint. Could be soluble in alcohol to form a transparent solution.

## Specifications

Item	Specification
Appearance	white powder
Methoxy(%)	19.0%-30.0%
Hydroxypropoxy(%)	4.0%-12.0%
Loss on drying	Max.5%
Average particle size	~80 μm
pH	4.0-8.0
Viscosity, Brookfield LV, 2% solution (20°C)	160000-240000mPa.s
Viscosity, Brookfield LV, 1% solution (20°C)	60000-70000mPa.s
Dispersing time	≤30sec.
Thickening time	≥5min

## Application Range

- Cleaning products
- Paint

## Key Properties

- Good ability as thickener

## Packaging and Storage

25kg multi-layer paper bags with an inner poethylene bag  
20'FCL:12 tons with pallets or 14 tons without pallets

3 years under cool, dry conditions in original packaging away from heat sources. It is recommended to use the product in rotation on a first-in first-out basis.

## **Safety Notes**

The above data is in accordance with our knowledge, but don't absolve the clients carefully checking it all immediately on receipt. To avoid the different formulation and different raw materials, please do more testing before using it. We reserve the right to alter our product and without informing in advance.

## **Company Information**

Shandong Charing Industry Co., Ltd.

Jinan City, Shandong Province, China

judie@sdcharing.com

www.sdcharing.com

**Shandong Charing Industry Co.,Ltd**

www.sdcharing.com

TEL/wechat/whatsapp:+86-150-6613-3527