

Product Description

Hydroxypropyl Methyl Cellulose CHARING HP 40M is medium viscosity construction grade hydroxypropyl methyl cellulose widely used in building materials. Could be soluble in water to form a transparent solution

Specifications

Item	Specification
Appearance	white powder
Methoxy(%)	19.0%-30.0%
Hydroxypropoxy(%)	4.0%-12.0%
Loss on drying	Max.5%
Average particle size	~80 μm
pH	4.0-8.0
Viscosity, Brookfield LV, 2% solution (20°C)	32000-48000mPa.s

Application Range

- Tile Adhesive
- Paste water resistant putty
- Dry-mixed plastering mortar
- Masonry mortar

Key Properties

- Improves workability
- Reduce water absorption
- Increase adhesion strength

Packaging and Storage

25kg multi-layer paper bags with an inner poethylene bag
20'FCL:12 tons with pallets or 14 tons without pallets

3 years under cool, dry conditions in original packaging away from heat sources. It is recommended to use the product in rotation on a first-in first-out basis.

Safety Notes

The above data is in accordance with our knowledge, but don't absolve the clients carefully checking it all immediately on receipt. To avoid the different formulation and different raw materials, please do more testing before using it. We reserve the right to alter our product and without informing in advance.

Company Information

Shandong Charing Industry Co., Ltd.

Jinan City, Shandong Province, China

judie@sdcharing.com

www.sdcharing.com

Shandong Charing Industry Co.,Ltd

www.sdcharing.com

TEL/wechat/whatsapp:+86-150-6613-3527