

**Redispersible Polymer powder
CHARING RD 7015H****Product Description**

CHARING® RD 7015H is a redispersible polymer powder produced by spray-drying special water-based emulsion, mostly based on vinyl acetate and ethylene. It dissolves in water easily and quickly forms emulsion.

Protective colloid Polyvinyl alcohol
Additives Mineral anti-block agents
CAS NO.:24937-78-8

Specifications

Appearance	white powder, free-flowing
Solid content	≥98.0%
Ash content	12%±2
Bulk density	400-600 g/l
Average particle size	~80 μm
pH value	5.0-8.0
MFFT	2°C
Tg	12°C

Application Range

- Tile adhesive/joint filler
- Skim Coat (Putty)
- Self-leveling mortar
- No Shrink Grout
- Repair mortar

Key Properties

- Increase adhesive/cohesive strength
- Higher flexural strength
- Excellent rheology
- Improved workability
- great durability and abrasion resistance

Shandong Charing Industry Co.,Ltd

www.sdcharing.com

TEL/wechat/whatsapp:+86-150-6613-3527

**Redispersible Polymer powder
CHARING RD 7015H**

- Improved water retention capability and open time

Packaging and Storage

A. Standard Packing: In 25kg bags out HDPE bags inner with LDPE bags

B. Big Bag or other special packages are possible on request.

Store it in a cool, dry place below 30°C and protected against humidity and pressing, since the product is thermoplastic, storage time should not exceed six months.

Safety Notes

The above data is in accordance with our knowledge, but don't absolve the clients carefully checking it all immediately on receipt. To avoid the different formulation and different raw materials, please do more testing before using it. We reserve the right to alter our product and without informing in advance.

Company Information

Shandong Charing Industry Co., Ltd.

Jinan City, Shandong Province, China

judie@sdcharing.com

www.sdcharing.com